



# SPECIAL LAUNCH PROMOTION



## FREE BLX-1 BATTERY WITH PURCHASE OF OM-1 Mark II

### CAMERA

### PROMO

OM-1 Mark II Body	FREE BLX-1 BATTERY
OM-1 Mark II + M.Zuiko 12-40mm F2.8 PRO II Kit	FREE BLX-1 BATTERY

## + SAVE \$300 WITH PURCHASE OF SELECT LENSES

LENS	PROMO	PHOTOGRAPHY GENRE
M.Zuiko 90mm F3.5 Macro IS PRO	\$300	Macro
M.Zuiko 40-150mm F2.8 PRO	\$300	Wildlife
M.Zuiko 100-400mm F5.0-6.3 IS	\$300	Bird
M.Zuiko 12-100mm F4.0 IS PRO	\$300	Landscape

Promo Term: 1/30 – 2/25/24



# Revealing wonder. it's in our NATURE.



## OM-1 Mark II

Nature is full of wonders waiting to be revealed. Those breathtaking scenes under unpredictable weather and fast-paced moments when encountering wildlife bring their own challenges, but they also offer the possibility to see and show them to the ones venturing further.

The OM SYSTEM OM-1 Mark II is a statement of blazing fast speeds, unparalleled computational capabilities, and tactile usability, with refinements throughout the camera. What the OM-1 Mark II presents is a true wonder of outdoor photography equipment that will perform wherever you go.

Revealing wonder. it's in our NATURE.

## FEATURES

---

**Computational Photography** that expands expression and hones image creation

---

**High Image Quality** that goes beyond expectation

**High-Speed Performance** for accurately capturing split-second moments

**Absolute Reliability**

**Video Functions** that meet the demands of creators

---

# SPECIFICATIONS

## OM-1 Mark II

SENSOR EFFECTIVE RESOLUTION / TYPE	20.4 Megapixel 4/3 Stacked BSI Live MOS
DUST REDUCTION	Super Sonic Wave Filter
PROCESSOR	TruePic™ X Dual Quad Core Processor
IMAGE STABILIZATION SYSTEM	5-Axis Image Stabilization with up to 8.5 Shutter Speed Steps Compensation
VIEWFINDER	Eye-level OLED electronic viewfinder, approx. 5.76M dots
REAR MONITOR	3.0-inch vari-angle monitor (electrostatic capacitance touch panel), Approx.1.62M dots (3:2)
WEATHERPROOFING	Dust, Splash and Freezeproof (IP53 Rated)
FOCUSING SYSTEM	High-speed imager AF: Imager phase detection AF and imager contrast AF used in combination
FOCUSING POINTS	Cross-type phase detection AF (1,053 points) Contrast AF (1,053 points) / All target Single target (1 point), Small target (9 points), Cross target (39 points) Middle target (63 points), Large target (165 points) Custom target* (AF area and its increment steps selectable)
AI DETECTION AF	Human, Formula cars, rally cars, motorcycles / Aircrafts, helicopters / Bullet trains, standard trains, steam locomotives / Birds / Dogs, cats
SEQUENTIAL SHOOTING	[Sequential shooting] approx 10 fps with selectable 1-10 fps [Anti-shock sequential shooting] approx 10 fps with selectable 1-10 fps [Silent sequential shooting] approx 20 fps with selectable 5, 10, 15, 20 fps without blackout [Silent sequential shooting SH1] approx 120 fps with selectable 60, 100, 120 fps without blackout *Slower shutter speeds and flash can not be used. [Silent sequential shooting SH2] approx 50 fps with selectable 12.5, 16.7, 25, 50fps without blackout *Compatible lenses are limited. [Pro Capture] approx 20 fps with selectable 5, 10, 15, 20 fps *When in Pro Capture mode, slower shutter speeds and flash can not be used [Pro Capture SH1] approx 120 fps with selectable 60, 100, 120 fps *When in Pro Capture mode, slower shutter speeds and flash can not be used [Pro Capture SH2] approx 50 fps with selectable 12.5, 16.7, 25, 50 fps *Slower shutter speeds and flash can not be used. *Compatible lenses are limited.
ADDITIONAL FEATURES	Focus Stacking Art Filters Live Composite Exposure Bracketing Live ND Live GND 4K Video Recording Wireless Shooting & GPS Info via Smartphone Vertical Video High Res Mode
WEIGHT	Approx. 511g (body only)
DIMENSIONS	Approx. 134.8mm(W) x 91.6mm(H) x 72.7mm(D)*Based on CIPA standards: excludes protrusions
BOX CONTENTS	Body, CB-USB13 USB cable, CC-1 Cable clip, CP-2 Cable protector, Shoulder strap, Instruction manual, Warranty card, BLX-1 Li-ion battery, F-7ACAC adapter, FL-LM3 Flash

To learn more about Olympus & OM SYSTEM products, please visit <https://explore.omsystem.com>

\*Specifications and appearances are subject to change without any notice or obligation on the part of the manufacturer. \*The colors of products printed herein may differ from those of the actual products. \*All other company and product names are registered trademarks and/or trademarks of their respective owners. \*The date herein is as of January 2024. © 2024 OM Digital Solutions



COMPARISON  
CHART

OM-1 Mark II



OM-5



E-M10 Mark IV

Image Processor	TruePic X	TruePic IX	TruePic VIII
Weatherproof Construction	IP53	IP53	
IS Compensation Steps (Body Only/ Sync IS)	8.5 / 8.5	6.5 / 7.5	4.5
Handheld High Res Shot	50MP (Selectable 12bit or 14bit)	50MP	
Live ND	ND2-ND128	ND2-ND16	
Live GND	X		
Interval Mode (Exposure Smoothing)	X	X	X
Starry Sky AF	X	X	
Face Detection AF / Eye Detection AF	X	X	X
Subject Detection AF	Birds, Animals, Humans, Planes, Trains and Vehicles		
Custom AF Target Mode	X	X	
Auto Focus Points	1053 points Cross-Type Phase Detection AF	121 points Cross-type Phase Detection AF	121 points Contrast Detection AF
MF Assist (Focus Indicator)	X	X	X
Custom Modes	Up to 4 mode dials, 15 buttons	Up to 4 mode dials, 11 buttons	Up to 3 buttons
My Menu	X	X	
Recording Time Limit	No Recording Time Limit	No Recording Time Limit	Up to 29 Minutes
Movie Picture Mode (OM - Log)	X	X	
Video Recording	C4K 60p/4K 60p/FHD 60p	C4K 24p/4K 30p/FHD 60p	4K 30p/FHD 60p
Vertical Video	X	X	
Wireless Remote Control	RM-WR1	RM-WR1	